## Amendments to the Abstract:

Please replace the Abstract with the following amended paragraph:

The present invention offers a A coherent light generating with extremely little low Fresnel device loss[[.]] Additionally, the invention makes anti-reflection coatings on the end surfaces of a wavelength-converting medium reducing deterioration unnecessary, while<del>also</del> anti-reflection coatings and wavelength-converting medium end surfaces, thereby improving the durability of the device. The invention relates to a coherent light <del>generating</del> <u>The</u>device <del>comprising an excitation beam</del> comprises a source for generating an excitation beam polarized in a predetermined direction\_[[; a]] wavelength-converting medium having a first end surface and a second end surface, for receiving receives the excitation beam incident on the a first end surface and outputting outputs from the a second end surface one or wavelength-converted beams polarized in the same direction as the predetermined direction.; and first First and second mirrors provided respectively at the first end surface and the second end surface of the wavelength-converting medium, for reflecting surfaces <u>reflect</u> wavelength-converted light emitted from the wavelength-converting medium and causing resonance thereof ... wherein the The first and second end surface is surfaces are oriented so that the excitation beam and the

wavelength-converted beam beams reflected respectively by the first and second mirror mirrors are incident at roughly the Brewster's angle, and the polarization of the excitation beam and the wavelength-converted beam beams is P-polarized with respect to the first and second end surface; and the surfaces second end surface is oriented so that the wavelength-converted beam reflected by the second mirror is incident at roughly the Brewster's angle, and the polarization of the wavelength-converted beam is P-polairized with respect to the second end surface.